



Phos-Out

Starves Algae of Nutrients!

KEEP OUT OF REACH OF CHILDREN

Eliminates Phosphates
Stops Recurring Algae Problems
Non-Toxic, All Natural

NET CONTENTS
32 FL. OZ (946 ml)

DIRECTIONS FOR USE

1. Start with chemically balanced water. (check pH, total alkalinity, and sanitizer levels)
2. If algae are present, superchlorinate pool water with Blue Wave Chlor-Burst or BlastOut Shock according to directions on product label. If no algae are present, treat the pool water with Blue Wave Blitz Shock (an oxygen source that does not contain chlorine) according to directions on product label. In biguanide pools, use dealer recommended shock treatment.
3. Brush pool surfaces and vacuum to filter. Allow pump to run during treatment.
4. Test for phosphates using a phosphate test kit.
5. Use chart below to determine correct dosage.
6. Shake container vigorously.
7. Slowly add proper amount of Blue Wave Phos-Out into skimmer with pump running.
8. Run filtration system for at least 24 hours. Check your filter pressure regularly. Backwash if necessary.
9. Wait 36 hours. If phosphates are still present, repeat procedure.
10. Use Blue Wave Phos-Out to maintain phosphate levels at or below 125 ppb.
11. Use 1 oz. per 5,000 gallons weekly to maintain phosphate levels at or below 125 ppb.

Match Gallons of Water with measured level of phosphate in chart below and add volume of phosphate remover found in appropriate box.

EXAMPLE: In a 20,000 gallon pool that tests for a phosphate level of 500 ppb, add 16 ounces of this product to the water.

DOSAGE CHART

	MEASURED LEVEL OF PHOSPHATES (PPB)			
	125	250	500	1,000
GALLONS OF WATER 5,000 10,000 15,000 20,000	1 oz.	2 oz.	4 oz.	8 oz.
	2 oz.	4 oz.	8 oz.	16 oz.
	3 oz.	6 oz.	12 oz.	24 oz.
	4 oz.	8 oz.	16 oz.	32 oz.

Distributed by:
Blue Wave Products
 St. Charles, Illinois
 60174
 1-800-759-0977

32 oz.

30 oz.

28 oz.

26 oz.

24 oz.

22 oz.

20 oz.

18 oz.

16 oz.

14 oz.

12 oz.

10 oz.

8 oz.

6 oz.

4 oz.

2 oz.